


Water-belt conveyor

Sturdy ■ Reliable ■ Easy to clean



Characteristics:

- ▶ Stainless steel (VA) tank, plastic belt
- ▶ Start stop control
- ▶ Water-tank feed line and water-tank drain through hand valve
- ▶ Separate water-tank cooling
- ▶ Water drain through the belt
- ▶ Leakage fuse



Components for your automation.

The component System



Choose the configuration you require:

Height of feeding section L_{Auf} : _____ mm Height of discharging section L_{Ab} : _____ mm
 Length of transport L_A : _____ mm Width of belt: _____ mm
 Cooling water- circulation: Yes No
 Height of slats: 20 mm 30 mm _____ mm
 Conveyor belt speed: 4 m/min. 9 m/min. 12 m/min.
 Directional control: Yes No
 Height of directional control: _____ mm
 Options: Controllable Sequential control system

Standard water-belt conveyor

Configuration:
400 V, 3 Ph., 50 Hz, ± 10 %

A+L-belt conveyors in different designs:

- | | |
|--|---|
|  Z-shaped belt conveyors |  Horizontal belt conveyors |
|  L-shaped belt conveyors |  Belt conveyors with storage bin |

Firm stamp

Subject to technical modifications. Availability and errors excepted · 234/10.10/GB